



Campus


CAMPUS LED IP20 G23 7,2W WH

Desk luminaire

The classic articulated Campus Led desk lamp is a great choice for a home office or a student's workspace. The lamp has an ergonomic design: the adjustable arm and head allow easy positioning of the light. The jointed structure reduces glare and improves ergonomics by letting you direct the light exactly where it's needed. Secure the lamp firmly to the edge of your desk using the screw clamp. The light source is a replaceable G23 LED bulb.

Campus Work point luminaire 7.2W 3000K 670lm No dim; Protection cl. II; L70B50 30000h; LED exchangeable; Lamp included; CRI>80; Housing al; Colour wh

CAMPUS LED IP20 G23 7,2W WH			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4107178	A1CACB	0.564	Campus



CAMPUS LED IP20 G23 7,2W WH

EC000302

Mounting	
Type of luminaire	Desk luminaire
Mounting method	Clamping
Suitable for wall mounting	No
Fit for workplace acc. EN 12464-1	No
Electrical connection with connector system	Yes
Structure	
Adjustable	Yes
Bendable	Yes
Adjustable height	Yes
Lamp type	LED exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	G23
Housing material	Aluminium
Housing colour	White
Cover colour	White
Control gear included	Yes
With switch	Yes
With socket outlet	No
Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming mains voltage modulation	No
Dimming manufacturer's proprietary system	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming potentiometer (integrated)	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming with push-button	No
Dimming Zigbee	No
No dimming function	Yes
With dimmer	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Photometric data	
Direct-/indirect proportion separately controllable	No
Light distributor	Reflector
Effective luminous flux (lm)	670
Photobiological safety according to EN 62471	RG1
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Colour rendering index (CRI/Ra)	80-89
Colour consistency (McAdam ellipse)	SDCM6
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No
Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	30000

Measurements	
Width (mm)	85
Height/depth (mm)	620
Length (mm)	333
Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Protection class according to IEC 61140	II
Suitable for lamp power (min) (W)	1
Suitable for lamp power (max) (W)	7.2
Maximum system power (W)	7.2
Power factor	0.7