




ALTA IP44 LED 20W/830 ANT

Alta Ceiling luminaire 20W 3000K 1800lm No dim;
IP44; Protection cl. I; L70B50 30000h; LED not
exchangeable; CRI>80; Ending; 3x1.5mm²; Housing al;
Colour ant; Cover Plastic, opal

ALTA IP44 LED 20W/830 ANT

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4126254	A1ALEA	1.55	Alta



Mounting	
Degree of protection (IP)	IP44
Suitable for ceiling mounting	Yes
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for surface mounting	Yes
Suitable for built-in mounting	No
Suitable for emergency lighting	No
Fit for monitor workplace	No
Connection type	Screwed terminal
Suitable for suspended mounting	No
Suitable for light line configuration	No
Number of poles	3
Conductor cross section (mm ²)	1.5
Type of wiring	Ending
Suitable for wall mounting	Yes

Structure	
With lamp	Yes
Colour housing	Anthracite
Material housing	Aluminium
Material cover	Plastic, opal
Lamp type	LED not exchangeable
Suitable for number of lamps	1
Lamp holder	Other
With air slots	No
Energy efficiency class of the built-in lamp	A++, A+, A (LED)
Housing surface protection	Powder coating
Emergency power supply integrated	No

Dimming and control	
With movement sensor	No
With light sensor	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI-2	No
Dimming DALI	No
Dimming DMX	No
Dimming potentiometer (integrated)	No
Dimming GPRS	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off	No
Dimming phase cut-on	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
Dimming DSI	No
Bluetooth operated	No
IFTTT support available	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No

Photometric data	
Effective luminous flux (lm)	1800
Colour temperature (max) (K)	3000
Colour temperature (min) (K)	3000
Colour rendering index CRI	80-89
Light outlet	Direct
Light sharing	Symmetric
Colour of light (alphanumeric)	White
Colour temperature switchable	No
Luminous flux adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C	30000
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-20
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	35

Measurements	
Length (mm)	250
Width (mm)	250
Height/depth (mm)	60

Electrotechnical data	
Type of control gear	LED operating device current-controlled
Nominal voltage (min) (V)	220
Voltage type	AC
Protection class	I
Suitable for lamp power (min) (W)	20
Maximum system power (W)	20
Nominal voltage (max) (V)	240
Suitable for lamp power (max) (W)	20
Luminaire efficacy (lm/W)	90