



-O  
3 x 2,5

IP44




# Flen Bollard

## IP44 13W/830 1300lm PCC ANT H1000

Flen Bollard Outdoor luminaire 13W 3000K 1300lm  
IP44; Protection cl. I; L70B50 30000h; LED not  
exchangeable; CRI>80; Ending; 3x2.5mm<sup>2</sup>; Housing al;  
Colour ant; Cover Plastic, transparent

IP44 13W/830 1300lm PCC ANT H1000			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4146688	A7GAMG	3.01	Flen Bollard



Mounting	
Type of luminaire	Bollard luminaire
Degree of protection (IP)	IP44
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm <sup>2</sup> )	2.5
Connection type	Other
Structure	
With base plate	Yes
Lamp type	LED not exchangeable
With lamp	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Aluminium
Material quality housing material	Other
Housing colour	Anthracite
Cover material	Plastic, transparent
Control gear included	No
Energy efficiency class of light source according to EU regulation 2019/2015	F
Dimming and control	
With light sensor	No
With movement sensor	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Photometric data	
Light distributor	None
Light sharing	Symmetric
Light outlet	Direct
Effective luminous flux (lm)	1300
Beam angle	Open beam
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Colour rendering index CRI	80-89
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No
Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	30000
Measurements	
Width (mm)	151
Height/depth (mm)	1000
Length (mm)	151
Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	Not required
Protection class	I
Suitable for lamp power (min) (W)	13
Suitable for lamp power (max) (W)	13
Maximum system power (W)	13
Luminaire efficacy (lm/W)	100
Power factor	0.9