

Pro

26W 50000h PEG BX

The Pro LED series tubes has been expanded with new T5 models. Two lengths are available: 1200 mm and 1500 mm. Both models feature a color temperature of 4000 K.

Opal T5 LED tube 26W 4000K G5 40000lm 50000h 19x1500mm, cardboard packing. Replaces 49W fluorescent tube. Operate only on 220-240 V AC power. Not compatible with electronic ballast. Supply frequency ~50/60Hz.



26W 50000h PEG BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4910414	A9LEAE	0.16	Pro

Mounting

Degree of protection (IP)	IP20
---------------------------	------

Structure

Colour	White
Housing colour	White

Dimming and control

Dimmable	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data

Luminous flux (min) (lm)	4000
Luminous flux (max) (lm)	4000
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Neutral 3300-5300 K
Colour temperature (min) (K)	4000
Colour temperature (max) (K)	4000
Beam angle (min) (°)	220
Beam angle (max) (°)	220
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG0

Lifetime and capacity**Measurements**

Diameter (mm)	19
Length (mm)	1500

Electrotechnical data

Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	127
Nominal current (max) (mA)	127
Power factor	0.9
Lamp power (min) (W)	26
Lamp power (max) (W)	26
Voltage type	AC